

EZ Door, Hormann

Product Group

Hollow Metal Doors

Product Type

Fire rated & Multipurpose door

Technical Data	Construction and quality features	Fire door	Multi-purpose door	Shaft door
Product Name				
Model number / Variants		FD	MPD	SD
Usage	Internal	●	●	●
	External			
Door sizes	Standard	1000 x 2100	1000 x 2100	750 x 1500
	Standard	1000 x 2400	1000 x 2400	900 x 1500
	Standard	1200 x 2100	1200 x 2100	750 x 1800
	Standard	1200 x 2400	1200 x 2400	900 x 1800
Material	Galvanised steel	●	●	●
Fire rating	Integrity (minutes)	120	-	120
Frame profile	(mm)	100 x 57	100 x 57	100 x 57
Profile	Non-grooved	●	●	●
Assembly	Mitered	●	●	●
Rebate stop	(mm)	19	19	19
Shutter thickness	(mm)	46	46	46
Infill	Honeycomb	●	●	●
Vision Panel 200 x 300mm	Fire rated 6mm	●	-	-
	Toughened glass 5mm	-	●	-
Undercut	(mm)	9	9	9
<u>Hardware</u>				
Hinges	Ball bearing Butt Hinges	●	●	●
Mortise sash lock	H11	●	●	-
Dead lock	H4	●	●	-
Shaft lock	H7	-	-	●
Lever handle	LT100	●	●	-
Pull Handle	D type 300mm	●	●	-
Flush Pull	Recessed type	-	-	●
Cylinder	Euro profile cylinder key x key	●	●	-
Panic device	Panic device XDB5760SV	●	●	-
Trim	External Trim	●	●	-
Door closer	Door closer HDC 03	●	●	-

● = Standard

○ = Optional

NA = Not available